

GPS SILICONE CSI 530

GENERAL PURPOSE SILICONE

ISO11600



- General Purpose Acetic cure silicone sealant
- Fast cure, highly flexible silicone rubber
- All purpose sealing and bonding
- Withstands 25 years of external weathering
- Bright glossy colours - low dirt pickup
- Good adhesion to PVCu extrusion and masonry

TYPICAL APPLICATIONS

- Frame sealing
- General bonding and weather sealing
- DIY
- Shower and bath sealing
- Glass and glazing

TECHNICAL SPECIFICATION

• TYPICAL UNCURED PROPERTIES

Specific Gravity	0.99
Application rate	42ml / Min
Sag	non sag
Tooling Time	5 Mins
Tack Free Time	10 - 25 Mins
Full Cure	2mm per day
Application Temperature	+5° C to +50° C

• TYPICAL CURED PROPERTIES

Hardness, Shore A	20
Modulus @ 100% Elongation	0.35 MPA
Elongation at Break	500%
Temperature Resistance	-50° C to +100° C

PACKAGING

- Packaging Volume 300ml
- 25 cartridges per box 1200 per pallet
- Colour White, translucent, brown



Sealants International Limited

Farndon Business Centre, Market Harborough
Leicestershire LE16 9NP, United Kingdom

Tel: +44 (0)1858 469936 Fax: +44 (0)1858 469917

e-mail: sales@sealants-int.com www.sealants-int.com