

LMN SILICONE CSI 330

LOW MODULUS NEUTRAL SILICONE

ISO11600



- Low Modulus Neutral silicone sealant
- Non corrosive, flexible, silicone rubber
- Soft and flexible, high quality sealing and jointing
- Longterm weathersealing for PVCu frame installations
- Excellent adhesion to non porous and porous surfaces
- Bright glossy colours – low dirt pickup – primerless

TYPICAL APPLICATIONS

- Perimeter pointing and weathersealing of PVCu, wood and aluminium frames
- General high movement bonding applications
- Sensitive surface bonding – mirrors, lead, plated, brass, copper, etc.
- Fungicide type available for sanitary work

TECHNICAL SPECIFICATION

• TYPICAL UNCURED PROPERTIES

Specific Gravity	1.00
Application Rate, g/min	300 (3.2mm x 6.3 BAR)
Sag ISO 7390	Non sag
Tooling Time (minutes)	10
Tack Free Time (minutes)	25
Full Cure	1–5mm per day 23°C @ 50% rH
Application Temperature	-30°C to +60°C

• TYPICAL CURED PROPERTIES

Hardness, Shore A	20	
Tensile Strength at Break	1.5	ASTM D-4112
Modulus @ 100% Elongation, MPA	0.37	N/mm ²
Elongation at Break, %	450	
Temperature Resistance	-40°C to +100°C	
Movement Accommodation	±25%	

PACKAGING

- | | |
|-------------------------|---------------------------|
| • Packaging Volume | 300ml |
| • 25 cartridges per box | 1200 per pallet |
| • Colour | White, translucent, brown |



Sealants International Limited

Farndon Business Centre, Market Harborough
Leicestershire LE16 9NP, United Kingdom

Tel: +44 (0)1858 469936 Fax: +44 (0)1858 469917

e-mail: sales@sealants-int.com www.sealants-int.com