

WB ACRYLIC CSI 430

WATER BASED ACRYLIC SEALANT

ISO11600



- Full cure, semi flexible, acrylic emulsion sealant
- Provides low to medium joint movement accommodation
- Internal trim and frame sealing for PVCu installations
- Good adhesion to plastic, masonry, plaster & wood
- Can be overcoated with all paints and wallcoverings

TYPICAL APPLICATIONS

- Interior pointing and sealing of PVCu, wood, aluminium – frames and trims
- General low movement sealing and gap filling applications – covings, dado rails, skirtings, architraves
- Fungicidal formulation for maximum performance.

TECHNICAL SPECIFICATION

• TYPICAL UNCURED PROPERTIES

Specific Gravity	1.6
Slump	None
Tooling Time (minutes)	10
Tack Free Time (minutes)	15–60
Full Cure (10mm x 10mm)	up to 28 days 23°C @ 50% rH
Application Temperature	+5°C to +45°C

• TYPICAL CURED PROPERTIES

Hardness, Shore A	50
Movement Accommodation	Low to medium but joints 12%
Service Temperature	-15°C to +60°C
Solids Content	80%
Chemical Resistance	Dilute acids & alkalines

PACKAGING

• Packaging Volume	300ml
• 25 cartridges per box	1200 per pallet
• Colour	White



Sealants International Limited

Farndon Business Centre, Market Harborough
Leicestershire LE16 9NP, United Kingdom

Tel: +44 (0)1858 469936 Fax: +44 (0)1858 469917

e-mail: sales@sealants-int.com www.sealants-int.com